

Instalatie de sablat tabla

Latime max. admisa a pieselor:	2.700 mm
Inaltime max. admisa a pieselor:	600 mm
Lungime min. admisa a pieselor:	2.400 mm
Sarcina max. la transportor:	1.600 kg/ml
Lungime transportor extern:	9.000 mm
Distanta intre role:	800 mm
Viteza de avans:	0,5 – 3 m/min
Viteza max. a abrazivului:	100 m/s

Masina de debitat cu gaz Omnimat CNC Messer Grisheim

Latime de lucru efectiv:	7.000 mm		
Lungime cale rulare:	18.000 mm		
Lungime utila:	14.000 mm		
Ecartament:	8.300 mm		
Viteza de avansare mm/min:	1	2	3
Mecanic:	100-1.200	1.000-6.000	5.000-12.000
Coordonate:	100-1.200	1.000-6.000	5.000-12.000

Masina de debitat cu CNC oxigaz tip OXYTOME 20 HPC

Dimensiune tabla:	2.000 x 6.000 mm
Grosime otel carbon:	2 – 30 mm
Grosime otel inox:	6 – 40 mm

Masina de roluit valt

Roluri cilindrice:	grosime max 80 mm; diametru min. 1.400 mm; latime 4.000 mm;
Roluri conice:	grosime max. 80 mm; diametru min. 1.400 mm; latime 3.000 mm;
Roluri de table:	grosime max. 25 mm; diametru min. 800 mm; latime 2.500 mm;

Masina de indoit Abkant LOD.D.315

Forta axiala:	315 t
Lungime masa:	4.000 mm
Latime masa:	200 mm

Inaltime de lucru:	6.300 mm
--------------------	----------

Grinda de sudare sub strat de flux

Curse utile:	rotatia montantului \pm 180o
Deplasare pe verticala:	- max. 850 mm (in jos) – max. 8000 mm (in sus)
Deplasarea pe orizontala:	stg-dr 750mm (de la capatul traversei)

Masina de debitat ComCut 31 Messer

Dimensiune tabla:	2.500 x 12.000 mm
Grosime tabla:	max. 30 mm
Viteza max.:	10.000 mm/min

Presă de indoit tabla PT 100 Abkant

Forta max.:	100.000 kg
Lungime max.:	3.550 mm
Lungime max. intre montanti:	2.550 mm